



## Shielding Braid QQB575 or A-A-59569

HOW TO READ THE SPEC:

<u>QQB575</u>	<u>R</u>	<u>36</u>	<u>T</u>	<u>0.375</u>
	Type			
Federal		AWG	Coating	Inside Diameter (Nominal)
Specification		Size		
	Type			
	R – Round ( Tubular )		T = Tinned Copper	
	F – Flat		S = Silver Plated Copper	

Dimensional Data						
RDS Wire Part Number	Flat Width nominal	AWG of Ends	Construction	Aprox. AWG Equiv.	Weight Lbs./1000' (Nominal)	Mil Spec P/N
<b>Flat Braids</b>						
QQBF -025-36	.025"	36	8 x 1 x 36	27	3	N/A
QQBF -062-36	3/32"	36	24 x 2 x 36	19	7	QQB575F36T062
QQBF -109-36	5/32"	36	24 x 4 x 36	16	11	QQB575F36T109
QQBF -125-36	1/8"	36	24 x 3 x 36	18	9	QQB575F36T078
QQBF -156-36	1/4"	36	24 x 10 x 36	12	23	QQB575F36T156
QQBF -187-36	3/16"	36	24 x 5 x 36	15	13	QQB575F36T125
QQBF -250-36	1/4"	36	24 x 7 x 36	14	18	QQB575F36T171
QQBF -375-30	3/8"	30	24 x 5 x 30	9	47	N/A
QQBF -375-36	3/8"	36	48 x 6 x 36	12	28	N/A
QQBF -500-30	1/2"	30	24 x 10 x 30	6	83	QQB575F30T437
QQBF -500-36	1/2"	36	48 X 8 X 36	10	39	N/A
QQBF -625-30	5/8"	30	24 x 15 x 30	5	121	QQB575F30T500
QQBF -625-36	5/8"	36	48 x 8 x 36	10	39	QQB575F36T375
QQBF -750-30	3/4"	30	24 x 20 x 30	3	170	N/A
QQBF -750-36	3/4"	36	48 x 18 x 36	7	75	QQB575F36T781
QQBF -875-30	7/8"	30	24 X 24 X 30	3	193	N/A
QQBF 1-000-36	1"	36	48 x 18 x 36	7	75	N/A
QQBF 1-375-30	1 3/8"	30	48 x 7 x 30	5	129	QQB575F30T875

**Other sizes and constructions are available. Consult our sales staff.**

For bare copper, add <u>BC</u> after the QQBx in the RDS part number:	i.e. QQBR <u>BC</u> -250-30
For Sliver plated copper, add <u>S</u> after the QQBx in the RDS part number:	i.e. QQBR <u>S</u> -250-36
For Nickel plated copper, add <u>N</u> after the QQBx in the RDS part number:	i.e. QQBR <u>N</u> -250-36
For Stainless Steel, add <u>SS</u> after the QQBx in the RDS part number:	i.e. QQBR <u>SS</u> -250-36

(Note: Stainless steel and NPC braids are not included on the QQB575 spec. The RDS part number is for reference only.)



Shielding Braid  
QQB575 or A-A-59569

Dimensional Data						
RDS Wire Part Number	Round I.D. nominal	AWG of Ends	Construction	Aprox. AWG Equiv.	Weight Lbs./1000' (Nominal)	Mil Spec P/N
<b>Round (Tubular) Braids</b>						
QQBR -062-32	1/16"	32	16 x 1 x 32	20	6	QQB575R32T062
QQBR -062-34	1/16"	34	16 x 2 x 34	19	8	QQB575R34T062
QQBR -062-36	1/16"	36	24 x 2 x 36	19	7	QQB575R36T062
QQBR -078-36	5/64"	36	24 x 3 x 36	18	9	QQB575R36T078
QQBR -109-32	7/64"	32	16 x 2 x 32	17	9	QQB575R32T109
QQBR -109-34	7/64"	34	16 x 4 x 34	16	12	QQB575R34T109
QQBR -109-36	7/64"	36	24 x 4 x 36	16	11	QQB575R36T109
QQBR -125-34	1/8"	34	24 x 3 x 34	16	12	QQB575R34T125
QQBR -125-36	1/8"	36	24 x 5 x 36	15	13	QQB575R36T125
QQBR -141-34	9/64"	34	24 x 4 x 34	15	17	N/A
QQBR -156-36	5/32"	36	24 x 10 x 36	12	24	QQB575R36T156
QQBR -171-34	11/64"	34	24 x 5 x 34	14	20	QQB575R34T171
QQBR -171-36	11/64"	36	24 x 7 x 36	14	17	QQB575R36T171
QQBR -203-34	13/64"	34	24 x 8 x 34	11	31	QQB575R34T203
QQBR -203-36	13/64"	36	24 x 13 x 36	11	31	QQB575R36T203
QQBR -250-34	1/4"	34	24 x 7 x 34	12	26	N/A
QQBR -250-36	1/4"	36	24 x 16 x 36	10	38	QQB575R36T250
QQBR -281-30	9/32"	30	24 x 5 x 30	9	47	QQB575R30T281
QQBR -375-30	3/8"	30	24 x 7 x 30	8	62	QQB575R30T375
QQBR -375-32	3/8"	32	48 x 3 x 32	11	38	QQB575R32T375
QQBR -375-36	3/8"	36	48 x 8 x 36	10	40	QQB575R36T375
QQBR -437-30	7/16"	30	24 x 10 x 30	6	85	QQB575R30T437
QQBR -500-30	1/2"	30	24 x 15 x 30	5	122	QQB575R30T500
QQBR -500-34	1/2"	34	48 x 7 x 34	9	53	QQB575R34T500
QQBR -500-36	1/2"	36	48 x 11 x 36	9	53	QQB575R36T500
QQBR -562-30	9/16"	30	48 x 10 x 30	3	156	QQB575R30T562
QQBR -625-34	5/8"	34	48 x 8 x 34	8	56	N/A
QQBR -656-30	21/32"	30	48 x 16 x 30	1	259	QQB575R30T656
QQBR -781-34	25/32"	34	48 x 11 x 34	7	77	QQB575R34T781
QQBR -781-36	25/32"	36	48 x 18 x 36	7	79	QQB575R36T781
QQBR -875-30	7/8"	30	48 x 7 x 30	5	123	QQB575R30T875
QQBR 1-000-30	1"	30	48 x 8 x 30	4	140	QQB575R30T1000
QQBR 1-250-30	1 1/4"	30	48 x 10 x 30	3	168	N/A
QQBR 1-000-30	1 1/2"	30	48 x 12 x 30	3	200	QQB575R30T1500
QQBR 2-000-30	2"	30	48 x 14 x 30	2	230	QQB575R30T2000